

XTREME POWER CONVERSION XPDU

Rack Power Distribution // 15A to 50A

For more information, visit www.xpcc.com/xpdu



Rack power distribution solutions designed to meet the needs of any data center or wiring closet

Improve data center power distribution with the XPDU family, a series of power distribution units that combine the key features needed to manage high density equipment racks or wiring closets.

XPDU's deliver reliable power distribution to multiple units of connected equipment by adding up to 24 receptacles to your rack space. These PDUs compliment your current power source and are compatible with any manufacturer's UPS.

PRODUCT SNAPSHOT

- › Available 120V models: 15A, 20A
- › Available 208V & 240/120V models: 30A, 50A
- › Vertical and horizontal configurations
- › UL, cUL, FCC, CE (varies by model)
- › 3 year full warranty (USA and Canada)

FEATURES

Plug and power—XPDU's provide up to 24 receptacles for power distribution

Receptacle control—switched model includes Web/SNMP interface with monitoring software and on/off control of eight receptacles

Hardwired models—input pigtail available with Basic XPD3 models

NEMA plugs and IEC inlet—multiple input configurations available

Branch circuit protection—UL1077 listed output circuit breaker

Mounting options—wall, rack, and floor mounting options available


Agency listed—UL, cUL, FCC, CE listings available (varies by model)

Transformer PDU—provides 208V to 120V step down

MODEL SELECTION GUIDE

For more information, visit www.xpcc.com/xpdu

MODEL NUMBER	Input Power Connection	Outlets	Voltage	Circuit Breaker	Dimensions (W x D x H)	Weight
Switched PDU						
XPD0815SL	Detachable 10 ft, 5–15P	(8) 5–15/20R	120V	15A	17 x 3.75 x 1.7 in (1U)	4.4 lbs
Transformer PDU with meter						
XPD-AT15A	Detachable 3 ft, IEC C14	(8) 5–15R front + (8) 5–15R rear	208V input 120V output	15A	19.0 x 10.5 x 3.5 in (2U)	19.7 lbs
Basic PDU - 15A & 20A models						
XPD815HV	12 ft, 5–15P	(8) 5–15R	120V	15A	17 x 3.75 x 1.7 in (1U)	2.6 lbs
XPD1415HV	12 ft, 5–15P	(14) 5–15R	120V	15A	17 x 3.75 x 1.7 in (1U)	3.5 lbs
XPD1420HV	12 ft, 5–20P + L5–20P	(14) 5–20R	120V	20A	17 x 3.75 x 1.7 in (1U)	4.8 lbs
XPDU-IEC	IEC C20 inlet	(2) IEC C19 + (10) IEC C13	230V	15/20A	17 x 3.75 x 1.7 in (1U)	4.4 lbs
Basic PDU - 30A & 50A models						
XPD24C13V	6 ft, L6–30P	(24) C13	208V	30A	66.0 x 1.8 x 1.8 in	12.0 lbs
XPD31	6 ft, L6–30P	(2) L6–30R + (2) L6–20R + (4) 6–15/20R	240V	30A	19.0 x 4.7 x 3.5 in (2U)	9.0 lbs
XPD32	6 ft, L6–30P	(2) L6–30R + (4) L6–20R	240V	30A	19.0 x 2.4 x 3.5 in (2U)	7.5 lbs
XPD33	6 ft, L6–30P	(4) IEC C19 + (8) IEC C14	240V	30A	19.0 x 2.4 x 3.5 in (2U)	6.0 lbs
XPD34	6 ft, L14–30P	(2) L6–30R + (4) L6–20R + (12) 5–20R	240/120V	30A	19.0 x 4.7 x 3.5 in (2U)	9.5 lbs
XPD35	Pigtail	(2) L6–30R + (4) L6–20R	240V	50A	19.0 x 2.4 x 3.5 in (2U)	7.0 lbs
XPD36	Pigtail	(4) IEC C19 + (8) IEC C14	240V	50A	19.0 x 2.4 x 3.5 in (2U)	6.8 lbs
XPD37	Pigtail	(2) L6–30R + (4) L6–20R + (12) 5–20R	240/120V	50A	19.0 x 4.7 x 3.5 in (2U)	10.0 lbs
Value PDU						
XPS1215HVP	6 ft, 5–15P	(12) 5–15R	120V	15A	17 x 1.5 x 1.7 in (1U)	1.4 lbs



X-TREME
Power Conversion®

Protect your business.

XPC USA / Denver, CO / sales@xpcc.com

XPC EMEA / Rotterdam, NL / emea@xpcc.com

www.xpcc.com

©2015 Xtreme Power Conversion Corporation. All Rights Reserved. XPDU.01U (Rev 10/12/15)