

# XPDU Xtreme Switched Power Distribution Unit



The **Xtreme Switched Power Distribution Unit** provides single-phase intelligent, monitored, switched power distribution to be used in power and control of multiple devices. An easy-to-read Meter provides True RMS readings to assure measurement accuracy. An RJ45 port allows for remote On/Off control of the individual output receptacles.

## Switched XPDU Features

- **On/Off Control of Individual Receptacles**  
Controlled power to 8 receptacles
- **Local Monitoring**  
Easy-to-read LED RMS Current Meter display provides a quick visual indication of the load, reducing the risk of overloads and tripped breakers.
- **Total Power Monitoring & Control**  
Meter, Web, SNMP  
Software included
- **Multiple Protocols**  
Http / Https / SNMP / DHCP / UDP
- **User-Defined Alarm Thresholds & Event Alerts**  
Delivered via Email, Trap, Audible Alarm
- **Branch Circuit Protection**  
UL1077 listed output circuit breaker
- **Space-Saving Mounting Options**  
Can mount horizontally in 1U, 0U, rack or wall mounting.  
Reserves traditional 1U space for IT equipment.  
Quick, easy installation with no additional mounting hardware or accessories to buy.
- **Standard Three-Year Warranty**  
Xtreme Power Conversion XPDU products are covered by a 3-year limited factory warranty.
- **Agency Listed**  
UL60950-1, cUL, FCC

*Xtreme value, Xtreme performance, Xtreme reliability*



## Switched XPDU SPECIFICATIONS

<b>Model</b>	<b>XPD-0815SL</b>
<b>Nominal Voltage</b>	<b>115VAC</b>
<b>Voltage</b>	<b>100 ~ 127 VAC full range</b>
<b>Frequency</b>	<b>50/60HZ full range</b>
<b>Max Input Current</b>	<b>15 AMP</b>
<b>Max Output Current</b>	<b>15 AMP</b>
<b>Input Connection</b>	<b>IEC 320 C19 to NEMA 5-15P 10 ft (3M)</b>
<b>Output Receptacles</b>	<b>(8) 5-15/20R individually controllable</b>
<b>Input Protection</b>	<b>15 AMP Circuit Breaker</b>
<b>Communication</b>	
<b>SSL Indication</b>	<b>(1) Yellow LED</b>
<b>DHCP Indication</b>	<b>(1) Green LED</b>
<b>Output Status</b>	<b>(8) Green LED</b>
<b>Network</b>	<b>(1) RJ45 for Ethernet</b>
<b>Current Meter</b>	<b>3 Digits for True RMS Meter</b>
	<b>Range: 0 ~ 20 AMP</b>
	<b>Resolution: 0.1 AMP</b>
	<b>Precision: <math>\pm 2\% \pm 0.1</math> AMP</b>
<b>Operating Temperature</b>	<b>32 - 104°F (0 - 40°C)</b>
<b>Operating Humidity</b>	<b>0 - 90%</b>
<b>Physical Size (W x D x H)</b>	<b>17.0 x 3.75 x 1.75 in (432 x 96 x 45 mm)</b>
<b>Weight</b>	<b>4.4 lbs (2 kg)</b>

